Technical Data Sheet





Page 1

EADHAir Duster

EADH is a non-flammable product designed for the safe removal of dust and airborne contamination from very delicate or inaccessible areas of electrical and electronic equipment. EADH contains a non-flammable, fluorinated propellant that combines the low GWP (global warming potential) of hydrocarbons with the ultra-low MIR (maximum incremental reactivity) and POCP (photochemical ozone creation potential) of hydrofluorocarbons.

- · Non-flammable, environmentally friendly propellant
- · Inert, pure compressed gas for dust removal
- Low GWP, MIR and POCP values
- · Ideal for removing particulates from inaccessible areas on delicate equipment

Typical Properties

Colour	Colourless
Flash Point (°C)	None
Boiling Point (°C)	-19
GWP (vs. CO ₂ , 100yr ITH)	6
Photochemical Reactivity (MIRg O ₃ /gVOC)	0.09
Photochemical Ozone Creation Potential (POCP)	6.4

<u>Description</u>	<u>Packaging</u>	Order Code	Shelf Life
EADH Airduster	200ml Aerosol	EADH200D	48 months
	400ml Aerosol	EADH400	48 months

Directions for Use

EADH should be used in a vertical position or at an angle of not greater than 60° to the vertical otherwise a freezing effect will result.

Caution: Do not use EADH for prolonged blasts as the surface of the can will form frost.

Revision 1: Jan 2014

Copyright Electrolube 2013

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Ashby Park, Coalfield Way, Ashby de la Zouch, Leicestershire LE65 1JR T +44 (0)1530 419 600 F +44 (0)1530 416 640 BS EN ISO 9001:2008 Certificate No. FM 32082